FU IPC BUIR 9901-AZ-M-AL 2.8-12 mm. IP Infrared Camera

AF Lens IR Bullet Net Camera

Key features

- 1/2.8" 2.0Mega progressive scan CMOS
- 2 Megapixel(1920x1080) Resolution
- Vari focal lens
- H.264 High Profile
- Support ROI, AGC, AWB, BLC, HLC
- Support intrusion detection
- Support audio,alarm,BNC output etc
- Support Triple-Stream,Mobile APP, Support P2P
- Support reset button
- Support 2D/3D DNR, DWDR , IR CUT Filter
- Support SD Card 64 GB
- Support DC 12 Volt,PoE(Power over Ethernet)
- Day & Night
- Support Motion Detector
- IP66(Water Proof)

Model	FU IPC BUIR 9901-AZ-M-AL 2.8-12 mm.
Camera	
Sensor	1/2.8"2.0Mega progressive scan CMOS
Min. Illumination	Colour:0.01Lux/F1.2; 0Lux/F1.2(IR ON)
Lens	2.8-12 mm. Varifocal lens
IR distance	50 M.
Electronic shutter	Auto(1/10s-1/10000s Adjustable)
Day/Night	Auto/Color / B&W(IR_CUT)
Anti-fog	Yes(On/Off)
Noise Reduction	2D/3D Digital Noise Reduction(Manual/Auto)
WDR	Digital WDR
Image Adjustment	Sharpness,Brightness,Saturation,Contrast Adjustable
PoE	Support
Compression Standard	
Video encoding	H.264 High Profile/Main Profile/BaseLine Profile
resolution	1920*1080@25fps/30fps
Triple-Steeam	sub-steram,third steram optional
Video Bitrate Control	Support reset button
Video Bitrate Range	32Kbps~ 8MKbps
Interface	
Audio I/O	1 Ch Audio In, 1Ch Audio Out
Alarm I/O	1 Ch Alarm In, 1Ch Alarm Out
Edge Storage	Built-in TF card slot,up to 64 GB
RS485	Yes
BNC Output	1 Ch BNC output
Reset Button	Support reset button
Network Interface	RJ45 10M/100M adaptive Ethernet interface
Features	
Smart Features	Support line-crossing detection;area intrusion detection;left baggage detection;object missing and left detection;retrograde motion detection;loitering detection; image virtual focuus deiection; camera shift detection; image color cast datection; face datection
Motion Detection	Multiple datection zones,variable sensitivity levels
Privacy Masking	Four zones for privacy masking
Snapshot	JPEG capture, capture resolution is the max coding resolition
Security Features	Suppoer password protection , watemarking features
Text Overlay	Support(Channel name and time title)
Alam	Support networkanomaly,mask alarm and etc.
Mobile App	IOS, Andriod
Network Function	TCP/IP,UDP,HTTP,IGMP,ICMP,RTP/RTSP,DNS,DDNS,FTP,NTP,PPPOE ,UPNP,SMTP,SNMP,PNP
Protocol	Support ONVIF and CGI protocol
General	
Protection Grade	IP66
Power	DC 12V/PoE
Operation Temperature	-20℃～+60℃
Operation humidity	10% -- 90%
Power supply	10W MAX
Installation	Bracket : Wall mounting/Ceiling
Dimensions	98*96*256(mm)
Weight	1160g