

Fu 203

Active Video Balun



Key features

- Single channel passive video Balun
- Support HDTV,HDCVI,Analog Camera
- Video transmission Via UTP CAT5
- Outstanding interference rejection
- Transient protection มีวงจรป้องกันฟ้าผ่า
- Transmit Distance:300M for AHD,CVI / 200M for TVI
- Exceptional Interference Rejection

Dimensions

Fu 203 Video Balun	ITEM	SPECIFICATION
Physical Properties	Dimension (L*W*H")	13.7 mm*11.6mm*3mm
	Shell	ABS
	Color	Black
Stability	N W	60g
	MTBF	>10000H
Stability Video	Operting Temperature	-10-55C
	Storage Temperature	-20-70C
	Humidity	0-95% (non-condensing)
Properties	Transmission signal	1 channel
Video transmission properties and port	Transmission distance	AHD/CVI:300m(max)
		TVI 200m(max)
	Cattegory Type	UTP CAT5/5E/6
	Coaxial video connector	BNC-M
	Twisted-pair video connector	Push-terminal
	Connector Format	AHD/HDTV/HDCVI
	Resolution	720P/1080P
	Anti-interference	>60db
Protection	ESD	1a contact discharge electricity level 3
		1b air discharge electricity level 3
Par:IEC61000-4-2		
Impedance	Coaxial cable Connector	2KV(common-code) Par:IEC 1000-4-5
	UTP Cable connector	2KV(different-code) 4KV(common-code) Par:IEC 1000-4-5
	BNC male	75 Ohms
	UTP cable	100 Ohms