

FU IPC BUIR 9901-AZ-M-AL 2.8-12 mm.

IP Infrared Camera

AF Lens IR Bullet Net Camera



Key features

- 1/2.8" 2.0Mega progressive scan CMOS
- 2 Megapixel(1920x1080) Resolution
- Vari focal lens
- H.264 High Profile
- Support ROI, AGC, AWB, BLC, HLC
- Support intrusion detection
- Support audio,alarm,BNC output etc
- Support Triple-Stream,Mobile APP, Support P2P
- Support reset button
- Support 2D/3D DNR, DWDR , IR CUT Filter
- Support SD Card 64 GB
- Support DC 12 Volt,PoE((IEEE 802.3af)
- Day & Night
- Support Motion Detector
- IP66(Water Proof)

Model		FU IPC BUIR 9901-AZ-M-AL 2.8-12 mm.
Camera		
Sensor	1/2.8"2.0Mega progressive scan CMOS	
Min. Illumination	Colour:0.01Lux/F1.2; 0.05Lux(Black/White), 0Lux/F1.2(IR ON)	
Lens	2.8-12 mm. Varifocal lens	
IR distance	50 M.	
Electronic shutter	Auto(1/10s-1/10000s Adjustable)	
Day/Night	Auto/Color / B&W(IR_CUT)	
Anti-fog	Yes(On/Off)	
Noise Reduction	2D/3D Digital Noise Reduction(Manual/Auto)	
WDR	Digital WDR	
Image Adjustment	Sharpness,Brightness,Saturation,Contrast Adjustable	
PoE	Support	
Compression Standard		
Video encoding	H.264 High Profile/Main Profile/BaseLine Profile	
resolution	1920*1080@25fps/30fps	
Triple-Stream	sub-stream,third stream optional	
Video Bitrate Control	Support reset button	
Video Bitrate Range	32Kbps~ 8MKbps	
Interface		
Audio I/O	1 Ch Audio In, 1Ch Audio Out	
Alarm I/O	1 Ch Alarm In, 1Ch Alarm Out	
Edge Storage	Built-in TF card slot,up to 64 GB	
RS485	Yes	
BNC Output	1 Ch BNC output	
Reset Button	Support reset button	
Network Interface	RJ45 10M/100M adaptive Ethernet interface	
Features		
Smart Features	Support line-crossing detection;area intrusion detection;left baggage detection;object missing and left detection;retrograde motion detection;loitering detection; image virtual focus detection; camera shift detection; image color cast detection; face detection	
Motion Detection	Multiple detection zones,variable sensitivity levels	
Privacy Masking	Four zones for privacy masking	
Snapshot	JPEG capture, capture resolution is the max coding resolution	
Security Features	Supporter password protection , watermarking features	
Text Overlay	Support(Channel name and time title)	
Alarm	Support network anomaly,mask alarm and etc.	
Mobile App	IOS, Andriod	
Network Function	TCP/IP,UDP,HTTP,IGMP,ICMP,RTP/RTSP,DNS,DDNS,FTP,NTP,PPPOE ,UPNP,SMTP,SNMP,PNP	
Protocol	Support ONVIF and CGI protocol	
General		
Protection Grade	IP66	
Power	DC 12V/PoE	
Operation Temperature	-20°C ~ +60°C	
Operation humidity	10% -- 90%	
Power supply	10W MAX	
Installation	Bracket : Wall mounting/Ceiling	
Dimensions	98*96*256(mm)	
Weight	1160g	