

Item		Description			
Products	Products	16 Ports Ethernet Switch	24 Ports Ethernet Switch	16 ports POE Ethernet Switch	24 ports POE Ethernet Switch
Power	Power Supply	Mains on load			
	Voltage Range	Ac 100 - 240 V, 50/60HZ			
	Consumption	30w	30w	320w	450
Network Connector	Ethernet Port	1 - 16/24 Ports: 10/100Mbps Ethernet port, adaptive control			
		UPLINK Ethernet ports: 10/100/100Mbps Ethernet port			
		SFP:SFP optical fiber module, 1000Mbps			
	Transmission Distance	1-16/24 ports: Recommended 120m Max. 150m ; Uplink 1000Mbps Ethernet port: Max.150mSFP : depend on yher optical module performace			
	PoE Protocol	N/A		IEEE802. 3af, IEEE802. 3at	
	PoE Power Supply	N/A		Ebd-span	
PoE Power Consumption	N/A		Each Port ≤ 30w , Total ≤ 270w	Each Port ≤ 30w , Total ≤ 390w	
Network Switch	Network Standard	IEEE802. 3 10BASE-T, IEEE802. 3u 100BASE-TX,IEEE802. 3ab 1000BASE-T, IEEE802. 3Z 1000BASE-SX\LX			
	MAC Table	16 K			
	Switch Capacity	11.2 Gbps	12.8 Gbps	11.2 Gbps	12.8 Gbps
	Throughput	8.33Mpps	9.52Mpps	8.33Mpps	9.52Mpps
Management	Management	Management L2			
Protection	ESD	Contact discharge: 6KV, Air discharge: 8KV; Per: IEC61000-4-2			
	Commmucation Port Lighting Protection	6KV,Per: IEC61000-4-5			
Environmental	Working Temperature	-10 °C ~ 50°C			
	Storage Temperature	-40 °C ~ 85°C			
	humidity (non-condensing)	8 ~ 95%			
Maechanical	Dimension (L x W x H)	442mm x 263mmx44.5mm			
	Material	Sheet metal			
	Color	Black			
	Weight	3.00kg	3.05kg	3.54kg	3.73kg