

FU All In One 1524-V2

HD DVR



- Embedded processor
- H.264 dual-stream video compression
- Recording 1080P, Output 1080P HDMI&VGA
- Audio In4, Out 1, 1RS-485
- Support HDCVI/AHD/TVI/CVBS/IP video inputs



Features

- เครื่องบันทึก Turbo 5 in 1 รองรับกล้องได้สูงสุด จำนวน 4 กล้อง
- รองรับระบบ HDTV I , HDCVI , AHD , CVBS , IP Camera
- ใช้สาย RG6 ในมาตรฐาน-ส่งสัญญาณภาพ ,เสียง , Control
- ระบบบีบอัดข้อมูลแบบ H.264 เมื่อบันทึก/อิมเมจ
- บันทึกความละเอียดสูงสุด 1080P ทุกช่องสัญญาณ
- Resolution Output 1920x1080P ผ่าน HDMI , VGA
- Port Audio In 4 , Audio Out 1, 1RS485
- รองรับ CVBS Output
- รองรับ Scan QR Code ดูข้อมูลารปัด Online
- รองรับ DDNS Peoplefu ไร้ แอจ เสถียร
- รองรับ HDD สูงสุด 6 TB (1 SATA)



Model		Fu All In One 1524-V2
System	Main chip	GM 8286
	OS	LINUX
	System Resources	Multi-channel Realtime recording, Multi-channel playback, Multi-channel network operation, USB Backup
Interface	Operation menu	16-bit true color graphical menu interface, mouse operation supported
	Display	1/4 display (take the pure coaxial input mode as an example)
Video	Format	H.264
	Output	CVBS; VGA; HDMI
	Preview	4*1080P@25fps
	Recode	4*1080P@15fps
	Decord	1*1080P@15fps
	Multi-mode Input	AHD: 4*AHD/TVI/CVI-NH; 4*960H Hybrid: 2*1080N(CVBS)+2*1080P(IP) AHD: 4*1080P
	Motion detect	Each view window can set 192 (16*12) detection area,can set multi-level sensitivity (only for local channel)
Audio	Audio	G.711A
	Intercom	Support
Recorind and Playback	Recording mode	Manual、Alarm、Motion Detect、Timer
	Local playback	4 Channel (when Analog mode)
	Video search	Time, Date,Event,Channel search
Storage and Backup	Storage	Local HDD, Network
	Backup	Network backup, external HDD, USB Drive, HDD
Port	Video Input	4 * BNC
	Video Output	1 * CVBS, 1 * VGA, 1 * HDMI
	spot monitor	NO
	Audio Input	4 * RCA
	Audio Output	1 * RCA
	Alarm Input	Optional (Max: 4 channels)
	Alarm Output	Optional (can be 1 channel)
	Network port	RJ45 10M/100M
	PTZ Control	1 * RS485 Support multipal PTZ Contract
	USB port	2 * USB2.0 port
	HDD Port	1 SATA port (Max 6TB)
Wireless Port	3G、WIFI(can be USB WIFI Dongle)	
Others	Power	1 * HDD: 12V/2A
	Power consumption	Less than 15W (no HDD)
	Working temperature	0℃—+55℃
	Working humidity	10%—90%
	Atmospheric pressure	86kpa—106kpa
	Size	171mm*78mm
	Weight	135g