


NVR5432-4KS2

NVR



Key Features

- เครื่องบันทึก NVR ต่อกำลัง IP Camera ได้สูงสุดจำนวน 32 กล้อง
- ใช้สาย LAN ในการรับ-ส่งสัญญาณภาพ, เสียง, Control
- ระบบการบีบอัดข้อมูลแบบ H.264, H.265
- เมนูภาษาอังกฤษ
- รองรับกล้อง IP Camera ที่ความละเอียดสูงสุด 12 ล้าน พิกเซล
- Resolution Output 4K/3840 x 2160 ผ่าน HDMI
- ฟังก์ชัน ค้นหาของหายอัจฉริยะ (Smart Search)
- ฟังก์ชัน Motion Detection / E-mail / FTP
- ฟังก์ชัน Privacy Mask การปกปิดพื้นที่ส่วนบุคคล
- ฟังก์ชัน Video Masking สัญญาณแจ้งเตือนเมื่อมีคนมาปิดหน้ากล้อง
- ฟังก์ชัน การแจ้งเตือนสัญญาณภาพของกล้องสูญหาย
- รองรับ Push Video
- รองรับ Two Way Talk Audio
- รองรับการดูผ่านบนระบบ P2P Cloud
- บนเว็บเบราว์เซอร์ที่ <https://www.easy4ip.com>
- โหมดการบันทึก Manual / Schedule / Motion Detection
- Dual Network
- Audio Format G711a
- รองรับ Harddisk 4 SATA Interface (Max HDD 24 TB)
- App Mobile สำหรับดูผ่านมือถือ People Fu Intelligent V.2 (Andriod) , gDMSS Lite (Andriod) , iDMSS Lite (iOS)
- สามารถรีโมทดูภาพปัจจุบัน,ย้อนหลัง, Backup ข้อมูลทาง Web Browser
- รองรับ 128 User กำหนดสิทธิ์การใช้งานได้อิสระ
- ได้รับการรับรองมาตรฐาน

- CE EN55022, EN55024, EN50130-4, EN60950-1
- FCC Part 15 Subpart B, ANSI C63.4-2014
- UL UL 60950-1 and CAN/CSA C22.2 No.60950-1



Model	NVR5432-4KS2
System	
Main Processor	Quad-core embedded processor
Operating System	Embedded LINUX
Video & Audio	
IP Camera Input	32 Channel
Two-way Talk	1 Channel Input, 1 Channel Output, RCA
Display	
Interface	2 HDMI (1 HDMI up to 3840x2160), 1 VGA
Resolution	3840x2160, 1920x1080, 1280x1024, 1280x720, 1024x768
Display Split	1/4/8/9/16/25/36
OSD	Camera title, Time, Video loss, Camera Lock, Motion detection, Recording
Recording	
Compression	H.265/H.264/MJPEG/MPEG4
Resolution	12Mp/8Mp/6Mp/5Mp/4Mp/3Mp/1080P/720P/D1& etc.
Record Bit Rate	320Mbps
Bit Rate	16Kbps - 20Mbps per channel
Record Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Record Interval	1-120 min (default: 60 min), Pre-record: 1-30 sec, Post-record: 10-300 sec
Video Detection Alarm	
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, FTP, Snapshot, Buzzer & Screen tips
Video Detection	Motion Detection, MD Zones: 396(22x18), Video Loss & Camera Blank
Alarm Input	16 channel
Relay Output	6 channel
Playback & Backup	
Sync Playback	1/4/8/16
Search Mode	Time/Date, Alarm, MD & Exact search (accurate to second), Smart search
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection, Digital zoom
Backup Mode	USB Device/Network/Internal SATA burner/eSATA Device
Network	
Interface	2 RJ-45 ports (10/100/1000Mbps)
Ethernet Port	2 Ethernet Ports Joint Working or 2 Independent 1000Mbps Ethernet Ports
Network Function	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPOE, DDNS, FTP, Alarm Server, IP Search(Support Dahua IP camera, DVR, NVS and etc.), P2P
Max. User Access	128 users
Smart Phone	iPhone, iPad, Android
Storage	
Internal HDD	4 SATA III ports, up to 6TB
External HDD	1 eSATA port
Auxiliary Interface	
USB	3 ports (2 Rear USB3.0, 1 Front USB2.0)
RS232	1 port, For PC communication&Keyboard
General	
Power Supply	Single, AC 100-240V, 50/60 Hz
Power Consumption	NVR : 16.7W
Working Environment	-10°C - +55°C / 10% - 90%RH / 86-106kpa
Dimension (WxDxH)	1.5U, 440mmx411.1mmx76mm
Weight	4.3KG